

PRODUCT INFORMATION



SOLID[®] SPECIAL BLOCKBOARD

SOLID Light 3 Layers

Deck	rotary cut veneer, HDF or chipboard
Core	fuma or albasia staves
Veneer types	fromager, poplar or beech
Glue	IF 20
Emission class	E1; E0 on request
Format	2070 x 2600/2800/5200 mm
Thickness	13/16/19/22/25/38/50 mm other thicknesses are available on request
Max. press format	2200 x 6300 mm
Moisture content	8 – 12%
Thickness tolerance	+ 0,2 mm – 0,6 mm
Tolerance in length and width	± 2 mm/m
Squareness tolerance	1 mm/m

Thickness in mm	kg/m ³	E-Modul (N/mm ²) (length)	E-Modul (N/mm ²) (width)	Bending strength (N/mm ²) (length)	Bending strength (N/mm ²) (width)
13	360	3600	3600	24	30
16	360	3600	3600	28	30
19	340	4200	4200	29	28
22	340	4500	4500	35	26
25	330	4800	4800	38	25
38					
50					

Multiple applications

HS Baco Panels offers the most suitable blockboard for each application.

A wide range of surface and cores ensure various alternatives. Additionally we develop solutions together with our customers, according to their individual requirements.

Significant advantages

- High stability and moisture resistance
- High bending strength
- Light weight
- High screw extraction resistance
- Easy processing

High quality

High quality raw material and longtime experience of our team are the basis for the outstanding quality of our blockboards.

Continuous quality controls ensure stable standards.

All wood that is processed by HS Baco Panels comes from PEFC™ controlled sources.

HS Baco Panels S.R.L.
Strada Crinului nr. 15, 605200 Comănești, România
T: +40 234 374 052
F: +40 234 374 622

baco.sales@hs.ro
www.hs.ro
www.hs.at