



HS TIMBER

PERFECTION IN TIMBER.


PRODUCTS

LOCATIONS

ABOUT HS TIMBER GROUP

HS Timber Group is a traditional wood processing company with Austrian roots and an international orientation.

We process coniferous roundwood in Europe and South America. Around 2,700 employees contribute to manufacturing tailor-made timber products for our customers. In addition to sawn timber production and sawn timber trading, we are also active in pellet production and bioenergy generation.



VIRASORO



KODERSDORF



LUVIA



RECI



RADAUTI



COMANESTI

PERFECTION IN TIMBER.

Getting better every day

SUSTAINABILITY

Our resource is renewable and unique. Through our engagement in the areas where we operate, we initiate and support the economic development of local communities and respect the environment.




PASSION

We are passionate and embrace new challenges to find the best solutions. Our ability to innovate, develop new products and services guarantees tailor-made solutions.



PARTNERSHIP

Good cooperation with partners is the secret of our joint success. Our reliability ensures the stability of our employees, suppliers and customers.



The sustainable industry

WOOD IS A SUSTAINABLE AND RENEWABLE RAW MATERIAL.


A sustainable supply chain - We know where our timber comes from.

WOOD IS SOURCED EXCLUSIVELY FROM SUSTAINABLY MANAGED AND LEGAL SOURCES.

Our goal: to purchase roundwood only from certified forests by 2030.

WOOD PRODUCTS STORE CO₂ FOR DECADES.

We use 100% of the roundwood.



SAWN TIMBER


Sawn Timber

Wood species	Spruce/fir and pine
Dimensions	Thickness 18 – 105 mm Width 30 – 300 mm Length 2000 – 5000 mm
Processing	Rough, anti-stain protection fresh or kiln-dried



Laths

Wood species	Spruce/fir and pine
Dimensions	Thickness 18 – 100 mm Width 18 – 100 mm Length 2000, 3000, 4000 and 5000 mm
Processing	Rough, anti-stain protection fresh or kiln-dried
Packaging	Mini tied



Packaging Timber

Wood species	Spruce/fir and pine
Dimensions	Thickness 12 – 22 mm Width 60 – 150 mm Length 800 – 5000 mm
Cut to size	On request eg. 800, 1000 or 1200 mm
Processing	Rough, anti-stain protection fresh or kiln-dried
Certification	Heat treated according to IPPC-Standard



Pallet Decks

Wood species	Spruce/fir and pine
Dimensions	According to customer requirements
Processing	Rough and kiln-dried
Certification	Heat treated according to IPPC-Standard



PLANED TIMBER

Planed Timber

Wood species	Spruce/fir and pine
Dimensions	Thickness 17 – 45 mm Width 80 – 300 mm Length 2000 – 5000 mm
Processing	Planed, square edged, eased edge, kiln-dried



Construction Timber

Wood species	Spruce/fir and pine
Dimensions	Thickness 18 – 105 mm Width 30 – 300 mm Length 2000 – 5000 mm
Processing	Planed, square edged, eased edge, kiln-dried
Certification	C16/24, JAS, PLIB, TPI, CMSA



GLUED TIMBER



Finger Jointed Door Stiles

Wood species	Spruce/fir and pine
Dimensions	Thickness 17 – 45 mm Width 25 – 200 mm Length up to 6000 mm
Glue	PVAc
Processing	Planed, square edged, chamfered, eased edge, KD 10 %



Finger Jointed Timber

Wood species	Spruce/fir and pine
Dimensions	Thickness 17 – 85 mm Width 25 – 200 mm Length up to 6000 mm
Glue	PVAc; HRA
Finger jointed	Surface or edge
Processing	Rough or planed KD 8 - 10 %
Packaging	Customised



Laminated Post & Beam

Wood species	Spruce/fir and pine
Dimensions	105 × 105 mm, 120 × 120 mm Length 2650 - 3985 mm 105 / 120 × 105 / 120 / 150 / 180 / 210 / 240 / 270 / 300 mm Length 2750 / 2985 / 3650 / 3985 mm
Glue	EPI; MF; MUF
Processing	Planed KD 12 %
Certification	JAS



PROFILED TIMBER

Profile Boards Trapezoid & Softline	
Wood species	Spruce/fir and pine
Dimensions	Thickness 12.5 / 14 / 19 mm Width 96 / 121 / 145 mm Main lengths 3000 and 4000 mm Retrimms 2000 and 2500 mm
Moisture	16 %
Packaging	Mini bundled, shrink wrapped
Certification	CE SR EN 14915:2013, 1870-CPR-1069/1



Garden House Profile	
Wood species	Spruce/fir and pine
Dimensions	Thickness 28 mm Width 116 / 145 mm Main lengths 3000 and 4000 mm Retrimms 2000 and 2500 mm
Moisture	16 %
Packaging	Mini bundled, shrink wrapped
Certification	CE SR EN 14915:2013, 1870-CPR-1069/1



Tongue & Groove	
Wood species	Spruce/fir and pine
Dimensions	Thickness 19 mm Width 145 mm Main lengths 3000 and 4000 mm Retrimms 2000 and 2500 mm
Moisture	16 %
Packaging	Mini bundled, shrink wrapped
Certification	CE SR EN 14915:2013, 1870-CPR-1069/1



Flooring	
Wood species	Spruce/fir and pine
Dimensions	Thickness 19 mm Width 145 mm Main lengths 3000 and 4000 mm Retrimms 2000 and 2500 mm
Moisture	12 %
Packaging	Mini bundled, shrink wrapped
Certification	CE SR EN 14915:2013, 1870-CPR-1069/1



PELLETS

Pellets	
Wood species	Untreated softwood
Quality	EN_plus A1 ISO 17225-2 (RO 002 & DE 056)
Caloric value	≥4.8 kWh/ kg
Diameter	6 mm +/- 1 mm
Water content	≤ 10.0 %
Packaging unit	Loose, big bags (approx. 1,100 kg), 15 kg bags



PELLETS - QUALITY

HS Timber Group produces pellets exclusively from sawmill by-products (sawdust, shavings and wood chips). This is also reflected in the high quality and low ash content.



Scan me
pellets Video

3-LAYER BLOCKBOARDS

SOLID Veneer 3-layer

Deck	Fromager, poplar or beech
Core	Spruce, pine, poplar or albasia staves
Glue	IF 20; AW 100 available on request
Emission class	E1/2; E0 on request
Format	1870 × 3130 / 3720 mm 2070 × 2800 / 4100 / 5200 / 5600 mm 1250 × 2500 mm 1220 × 2440 mm
Thickness	13 / 16 / 18 / 19 / 22 / 25 / 28 / 38 mm Other thicknesses are available on request
Max. press format	2200 × 6500 mm



SOLID HDF 3-layer

Deck	HDF
Core	Spruce, pine or poplar staves
Glue	IF 20; AW 100 available on request
Emission class	E1/2; E0 on request
Format	3720 × 1870 mm 5600 / 5200 / 2800 × 2070 mm 2500 × 1250 mm 2440 × 1220 mm
Thickness	15 / 16 / 18 / 19 / 22 / 25 / 29 / 30 / 38 mm
Max. press format	6500 × 2200 mm



SOLID Chipboard 3-layer

Deck	Thin chipboard
Core	Spruce, pine or poplar staves
Glue	IF 20; AW 100 available on request
Emission class	E1/2; E0 on request
Format	5600 / 5200 / 2600 × 2070 mm
Thickness	16 / 18 / 19 / 22 / 25 / 38 mm Other thicknesses are available on request
Max. press format	6500 × 2200 mm



SOLID Laminboard Core 3-layer


Deck	Rotary cut veneer, HDF or chipboard
Core	2 - 5 mm strips of spruce, pine, poplar or light wood
Veneer	Fromager, poplar, beech
Glue	IF 20; AW 100 available on request
Emission class	E1/2; E1 ; E0 on request
Format	2070 × 2600 / 5200 / 5600 mm 1250 × 2500 mm
Thickness	16 / 18 / 19 / 22 / 25 / 28 / 38 mm Other thicknesses are available on request
Max. press format	2200 × 6500 mm




Other formats on request.



Scan me




High stability and bending strength



Light weight



High screw extraction resistance



BLOCKBOARDS SPECIALS

SOLID Light 3-layer

Deck	Rotary cut veneer, HDF or thin chipboard
Core	Albasia staves
Glue	IF 20; AW 100 available on request
Emission class	E1/2; E0 on request
Format	2070 × 2600 / 5200 mm
Thickness	13 / 16 / 19 / 22 / 25 / 38 / 50 mm Other thicknesses are available on request
Max. press format	2200 × 6500 mm



SOLID Melamine 3-layer

Deck	4 mm chipboard or HDF melamine covered
Core	Spruce, pine, albasia or poplar staves
Decor	On request
Glue	IF 20; AW 100 available on request
Emission class	E1/2; E0 on request
Format	5400 / 5200 / 3720 / 2800 / 2600 × 2030 mm
Thickness	16 / 19 / 20 / 22 / 25 / 30 mm Other thicknesses are available on request
Max. press format	5400 × 2030 mm



SOLID Prime 3-layer

Deck	Rotary cut veneer, HDF or thin chipboard
Core	Spruce, pine or poplar staves, light core
Decor	White paper impregnated with aminoplast resins
Glue	IF 20
Emission class	E1/2; E0 on request
Format	2070 × 2600 / 5200 mm
Thickness	13 / 16 / 19 / 22 / 25 / 38 mm Other thicknesses are available on request
Max. press format	2070 × 5400 mm



SOLID Decorative Veneer 5-layer

Decor	Sliced cut decorative veneer beech, oak, maple, poplar, cherry, ash, alder, lime, birch other species available on request
Core	Spruce, pine or poplar staves
Deck	Rotary cut veneer or HDF
Glue	IF 20
Emission class	E1/2; E0 on request
Format	3100 × 1850 mm, 2600 × 2060 mm 2500 × 1250 mm
Thickness	16 / 19 / 22 mm Other thicknesses are available on request
Max. press format	3100 × 2070 mm



5-LAYER BLOCKBOARDS

SOLID Double Core 5-layer

Deck	Rotary cut veneer fromager, poplar or beech
Core	Spruce, pine or poplar staves Also available in light core
Glue	IF 20; AW 100 available on request
Emission class	E1/2; E0 on request
Format	1870 × 2200 / 2250 mm 1250 × 2200 / 2500 mm
Thickness	34 / 39 / 41 / 44 / 47 / 50 mm Other thicknesses are available on request
Max. press format	2200 × 6500 mm



SOLID HDF Double Core 5-layer

Deck	HDF or thin chipboard
Core	Spruce, pine or poplar staves Also available in light core
Glue	IF 20; AW 100 available on request
Emission class	E1/2; E0 on request
Format	3720 × 1870 mm 5600 / 5200 / 2800 × 2070 mm 2500 / 2200 × 1250 mm 2440 × 1220 mm
Thickness	34 / 39 / 41 / 44 / 50 mm Other thicknesses are available on request
Max. press format	6500 × 2200 mm



SOLID HDF Triple Core 5-layer

Deck	HDF or thin chipboard
Core	Spruce or poplar staves Also available in light core
Glue	IF 20; AW 100 available on request
Emission class	E1/2; E0 on request
Format	3050 × 1250 mm 2600 × 2070 / 1850 mm 5600 / 5200 × 2070 / 1850 mm
Thickness	34 / 39 / 41 / 44 / 50 mm Other thicknesses are available on request
Max. press format	6500 × 2200 mm



SOLID Double Veneer 5-layer

Deck	Rotary cut veneer poplar, fromager
Core	Spruce, pine or poplar staves
Underdeck	Poplar or Fromager
Glue	IF 20; AW 100 available on request
Emission class	E1/2; E0 on request
Format	1870 × 3130 / 3720 mm
Thickness	18 / 20 / 25 / 30 mm Other thicknesses are available on request
Max. press format	2200 × 6500 mm




Other formats on request.

BIG SIZE – SHUTTERING PANELS

BLOCKBOARD CORE

FORM XL 3 – S STAB 180 3-layer

Format/Size	2000 × 5400 × 21 mm
Glue	AW 100
Edge	Rectangular cut, sealed edges
Coating	Concrete pour side 180g/ m², coating rear side 120g/ m²
Average number of pours	15
Weight	10.5 kg/ m²
Modulus of elasticity*	Lengthways 5660 N/ mm², crossways 6640 N/ mm²
Bending strength*	Lengthways 30 N/ mm², crossways 35 N/ mm²
Pieces per pallet	25



BLOCKBOARD CORE

FORM XL 3 – S STAB 450 3-layer

Format/Size	2000 × 5400 × 21 mm
Glue	AW 100
Edge	Rectangular cut, sealed edges
Coating	Concrete pour side 450g/ m², coating rear side 450g/ m²
Average number of pours	25
Weight	11 kg/ m²
Modulus of elasticity*	Lengthways 5,660 N/ mm², crossways 6,640 N/ mm²
Bending strength*	Lengthways 30 N/ mm², crossways 35 N/ mm²
Pieces per pallet	25



LAMINBOARD CORE

FORM XL 3 – S STAE 450 3-layer

Format/Size	2000 × 5400 × 21 mm
Glue	AW 100
Edge	Rectangular cut, sealed edges
Coating	Concrete pour side 450g/ m², coating rear side 180g/ m²
Average number of pours	30
Weight	11 kg/ m²
Modulus of elasticity*	Lengthways 5,000 N/ mm², crossways 7,700 N/ mm²
Bending strength*	Lengthways 32 N/ mm², crossways 41 N/ mm²
Pieces per pallet	24



LAMINBOARD CORE

FORM XL 5 - S STAE 450 5-layer

Format/Size	2000 × 5400 × 21 mm / 27 mm
Glue	AW 100
Edge	Rectangular cut, sealed edges
Coating	Concrete pour side 450g/ m², coating rear side 450g/ m²
Average number of pours	40
Weight	11 - 13.5 kg/ m²
Modulus of elasticity*	Lengthways 4,220 N/ mm², crossways 7,400 N/ mm²
Bending strength*	Lengthways 45 N/ mm², crossways 36 N/ mm²
Pieces per pallet	24/ 18



* Indicated figures are only standard values.

EDGE GLUED PANELS

DIY Edge Glued Panels

Wood species	Spruce or pine
Glue	D3 according to DIN EN 204
Thickness	18 / 27 mm
Dimension	Widths 200 / 250 / 300 / 400 / 500 / 600 / 800 and 1000 mm Lengths 800 / 1000 / 1200 / 1500 / 2000 / 2500 and 3000 mm
Surface	Sanded (120 grid)
Moisture	10 %
Lamella width	30 - 50 mm
Packaging	Single shrink wrapped Customised label on request



Large-Format Edge Glued Panels

Wood species	Spruce or pine
Glue	D3 according to DIN EN 204
Thickness	18 / 27 mm
Dimension	1220 × 2000 / 2500 / 3000 mm
Surface	Sanded (120 grid)
Moisture	10 %
Lamella width	40 - 60 mm
Packaging	Single shrink wrapped Customised label on request



LUVIA PRODUCTS



Profiled Timber Fase

Wood species	Spruce
Dimensions	22.5 × 121 mm (nom 25 × 125 mm) 3000 – 6000 mm
Moisture	18 %
Surface	Untreated
Packaging	Shrink wrapped



Profiled Timber UTV

Wood species	Spruce
Dimensions	20 × 120 mm (nom 22 × 125 mm) 3000 – 6000 mm
Moisture	18 %
Surface	Untreated or primed white, Teknol 2881
Packaging	Shrink wrapped



Profiled Timber Glattkant

Wood species	Spruce/ Pine
Dimensions	18 × 95 mm (nom 22 × 100 mm) 3000 – 6000 mm
Moisture	18 %
Surface	Untreated
Packaging	Shrink wrapped



Profiled Timber TGV

Wood species	Spruce
Dimensions	22 × 120 mm (nom 25 × 125 mm) 3000 – 6000 mm
Moisture	18 %
Surface	Untreated or coated black, Nordica Eco RAL 9005
Packaging	Shrink wrapped



Profiled Timber STV DIN

Wood species	Spruce
Dimensions	19.5 × 96 mm (nom 22 × 100 mm) 3000 – 6000 mm
Moisture	18 %
Surface	Untreated or primed white, Teknol 2881
Packaging	Shrink wrapped



Profiled Timber Klink

Wood species	Spruce
Dimensions	17,5 × 146 (nom 19 × 150 mm) 3000 – 6000 mm
Moisture	18 %
Surface	Untreated or primed and surface-treated white, Nordica Eco 3330-03 NCS S 0502-Y
Packaging	Shrink wrapped



PINIERA PRODUCTS



Packaging Timber

Wood species	Taeda / Elliotti Pine
Dimensions	Thickness 13 – 22 mm Width 60 – 150 mm Length 800 – 3100 mm
Moisture	KD 12 – 14 %
Certification	Heat treated according to IPPC-Standard
Processing	Rough or planed



Sawn Timber / Construction Timber

Wood species	Taeda / Elliotti Pine
Dimensions	Thickness 17 – 75 mm Width 60 – 250 mm Length 800 – 3100 mm
Moisture	KD 8 – 14 %
Certification	KD HT
Processing	Rough or planed



Furniture Grade / COL

Wood species	Taeda / Elliotti Pine
Dimensions	Thickness 17 – 50 mm Width 60 – 250 mm Length 800 – 3100 mm
Moisture	KD 8 – 14 %
Processing	Rough, planed, square edged, eased edged



Planed Timber

Wood species	Taeda / Elliotti Pine
Dimensions	Thickness 17 – 50 mm Width 60 – 250 mm Length 800 – 3100 mm
Moisture	KD 8 – 14 %
Processing	Planed, square edged, eased edged



Clear Timber

Wood species	Taeda / Elliotti Pine
Dimensions	Thickness 17 – 75 mm Width 60 – 250 mm Length 800 – 3100 mm
Moisture	KD 8 – 14 %
Processing	Rough, planed, square edged, eased edged



Appearance Boards

Wood species	Taeda / Elliotti Pine
Dimensions	Thickness 17 – 22 mm Width 89 / 140 / 184 / 235 mm Length 800 – 3100 mm
Moisture	KD 12-14 %
Processing	Planed, square edged, eased edged



PERFECTION

IN CUSTOMER SERVICE

OUR GOAL:

To meet and exceed customer expectations. As a team, it is our job to do so – right down to the very last detail. Our sales team appreciates special requests as these give us the opportunity to work with our customers on new ideas and innovations.

Contact

AUSTRIA

HS Timber Group GmbH

Favoritenstraße 7/2

1040 Vienna

T +43 (0) 1 585 68 62-0

F +43 (0) 1 585 68 62-20

office@hs.at

Piniera GmbH

Favoritenstraße 7/2

1040 Vienna

office@piniera.com

ROMANIA

HS Baco Panels S.R.L.

Strada Crinului Nr. 15

605200 Comănești

T +40 (0) 234 374 052

baco@hs.ro

FINLAND

Luvian Saha Oy

Sahantie 1

29100 Luvia

T +358 20 779 1100



Scan me



www.hs.at

www.luviansaha.fi

www.piniera.com

© **HS Timber Group GmbH**

Favoritenstraße 7/2

1040 Vienna

Austria

Status as of: June 2024



gedruckt nach den Richtlinien des
Österreichischen Umweltzeichens,
Druckerei Janetschek GmbH
UW-Nr. 637