

GENERAL LUMBER PURCHASE CONDITIONS – HS TIMBER PRODUCTIONS S.R.L.

CUTTING SIZE (mm)	KD INVOICE SIZE (mm)	LENGTH (m)	SPECIES	DESCRIPTION
47/53x9 7/117/134	45/50 x 92/111/127	2.1/2.4/2.7/3/3.5/3.8/4/4.5/5	Spruce / Pine	Quality O/III: main cut from good logs quality. KD: 12% (+/-2%) Quality description: sharp edged, separated-core produced, 2 or 4 pieces, generally healthy knots isolated black knots till max. 30mm allowed, without coloration, without insects, without fibre deviation, only isolated resin pockets, easy drying cracks allowed.
27 x 115	25 x 110	2.7/2.9/3/3.35/3.7/4	Spruce	Quality O/III: main cut from good logs quality.
30 x 131	28 x 125	2.7/2.9/3/3.35/3.7/4	Spruce	KD: 12% (+/-2%)
32 x 117	30 x 112	2.8/3/3.7/4	Spruce / Pine	Quality description: sharp edged, cut from core, double width cut is not allowed, generally healthy knots isolated black knots till 30 mm allowed, without colorations, without insects, without fibre deviation, only isolated resin pockets . Drying cracks are not allowed.
36 x 117	34 x 112	2.8/3/3.7/4	Spruce / Pine	
36 x 133	34 x 127	2.8/3/3.7/4	Spruce / Pine	
27-53 x 95-370	25-50 x 90-350	1 - 6	Spruce / Pine	Quality IV/V KD: 10% (+/-2%) Quality description: Rejected quality. It is accepted blue stain and other healthy coloration. Not accepted: mould, brown mouldy coloration (soft), choked wood, compression wood, clogged bark, and longitudinal cracks.

Tolerance: thickness/width -0/+2mm and length -0/+8 mm
Overlength: minimum 30 mm
All sizes can be also delivered fresh

CUTTING SIZE (mm)	KD INVOICE SIZE (mm)	LENGTH (m)	SPECIES	DESCRIPTION
85 x 85	85 x 85	3.05 / 4.05	Spruce	Quality O/III: main cut from good logs quality.
108 x 108	108 x 108	3.05 / 4.05	Spruce	Quality description: sharp edged, generally healthy knots and isolated black knots with diameter till maximum 30 mm allowed, without coloration, without insects, without fibre deviation, isolated resin pockets 5x50 mm/ml. Straight end-cracks allowed max. 50mm. Fir is not allowed. Bark allowed 50 mm diagonal one side.
108 x 128	108 x 128	3.05 / 4.05	Spruce	
108 x 142	108 x 142	4.05	Spruce	

Tolerance: thickness/width -0/+2mm and length -0/+100mm
Overlength: minimum 50 mm
All sizes can be also delivered fresh