

## Veneer Conditions for HS Baco Panels, Romania

Type (Species)	Peeled Fromager veneer (Ceiba Petandra)	Peeled Ilomba veneer (Pycnanthus Angoleis)	Peeled poplar veneer	Peeled beech veneer
<b>Short grain [mm]</b>	1270 x 2540* mm 1900 x 3160* + mm 2080 x 5240* + mm	2050 x 500 mm	1300 x 2600 mm 1900 x 1850 mm	1300 x 2600 mm 2030 x 1030
<b>Thickness [mm]</b>	2.0 and 2.2 mm	2.2 mm	1.5, 1.8 and 2.0 mm	2.0 mm
<b>Moisture Content [%]</b>	8 +/- 2%	8 +/- 2%	8 +/- 2%	8 +/- 2%
<b>Delivery</b>	CIF Constanța	CIF Constanța	EXW/delivered to Comănești	EXW/delivered to Comănești
<b>Quality</b>	Blockboard faces/backs of sound wood, no open defects, correctly peeled, cut should be smooth and with even thickness, no rough cut or tear grain, free of decay and worm or insect attack.	Blockboard faces/backs of sound wood, no open defects, correctly peeled, cut should be smooth and with even thickness, no rough cut or tear grain, free of decay and worm or insect attack.	Blockboard Faces/Backs (A/B), Interior Quality	Blockboard Faces/Backs (A/B)

\* Min. 80% full sheets, 20% part widths accepted in 1270/840/640